

RF3323 Ash-free Antioxidant

• Product Introduction

RF3323 Antioxidant is a kind of multipurpose ash-free additive. It not only boasts outstanding anti-oxidation performance, but also has great abrasion resistance and extreme pressure properties. Meanwhile, it has excellent compatibility with other additives. This product can be used in steam turbine oil, hydraulic oil, gear oil, internal combustion engine oil and other variety of oils to improve their anti-oxidation and abrasion resistance. It's also an effective extreme-pressure additive for lubricating grease.

• Product Technical Index

Item	Index	Test Method
Appearance	Light yellow green /Light brown transparent liquid	Visual Inspection
Flash Point (COC), °C	≥180	ASTM D92
Kinematic Viscosity (100°C), mm ² /s	15.0-17.0	ASTM D445
Density (20°C), kg/m ³	1050-1100	ASTM D4052
N Content, m%	6.30-7.00	ASTM D3228
S Content, m%	26.50-32.50	ASTM D1552
Color Number	≤2.0	ASTM D1500

• Package, Storage and Transportation

The product is packed with iron barrels, 200kg/barrel or other packing methods consulting with clients.

Suitable for truck transport, railway transport and ocean transport.

The temperature of storage and transportation shall not surpass 45°C. The shelf life of product is 2 years.

The product is non-toxic and non-corrosive, can be thoroughly washed out with detergent in case of contact with skin accidentally.