

## RF6133 SE/SF Gasoline Engine Oil Package

### • Product Introduction

RF6133 is gasoline engine oil package blended by various kinds of additives, such as superior detergent, dispersant, antioxidant/corrosion inhibitor etc. The gasoline engine oil prepared from RF6133 has excellent lubricity, detergency, dispersity, anti-oxidation and anti-corrosion ability.

### • Recommended Dosage

API Performance Level	SAE Viscosity Grade	Treating Rate (mass%)
SE	15W/40	4.0%
SF	15W/40, 10W/30	4.3%

### • Product Quality Characteristics & Test Method

Item	Typical Value	Test Method
Appearance	Brown viscous liquid	Visual Inspection
Density (20°C), kg/m <sup>3</sup>	1007	ASTM D4052
Kinematic Viscosity (100°C), mm <sup>2</sup> /s	129	ASTM D445
Flash Point (COC), °C	≥190	ASTM D92
Total Base Number, mgKOH/g	97	ASTM D2896
N Content, m%	0.8	ASTM D3228
Zn Content, m%	2.3	ASTM D4951
Ca Content, m%	3.1	ASTM D4951
P Content, m%	1.8	ASTM D4951

### • Product Storage/Handling/Transportation/Package

The storage temperature should not exceed 50°C, the loading/unloading and blending temperature should not exceed 60°C.

It is not flammable, not explosive, not corrosive, in the items of safety, environment protection, use, etc., it is same as normal petroleum product, with no special protection. Product package: The product is packed with 200 litre iron drum or according to user's requirement. Specific weight of delivery is subject to the actual filling weight.