

RF6163 Two-stroke Motorcycle Oil Package

• Product Introduction

This product made by selected high-quality detergent, dispersant. Has a good detergency, lubricity, low ash, excellent smoke extraction and other performance. This product is used to modulate FB, FC quality grade air-cooled two-stroke gasoline engine oil, accord with JASO M345 FB, FC performance index.

• Recommended Dosage

Performance Level	Treating Rate (mass%)
FB	4.0%
FC	5.5%

• Product Quality Characteristics & Test Method

Item	Typical Value	Test Method
Appearance	Brown viscous liquid	Visual Inspection
Density (20°C), kg/m ³	Report	GB/T13377, ASTM D4052
Kinematic Viscosity (100°C), mm ² /s	Report	GB/T265, ASTM D445
Flash Point (COC), °C	≥180	GB/T3536, ASTM D92
Total Base Number, mgKOH/g	32	SH/T0251, ASTM D2896
N Content, m%	0.9	SH/T0224, ASTM D3228
Ca Content, m%	0.5	GB/T17476, ASTM D4951

• Product Storage/Handling/Transportation/Package

Product storage temperature should not exceed 50 °C, the maximum temperature does not exceed 60 °C when handling and modulating;

This product is not flammable, non-explosive, non-corrosive, it is same as general petroleum products in safety, environmental protection, use and other aspects, no need the special protection.

Product packaging: 200L metal drum or according to user requirements packaging, the specific weight to the actual prevail.

FOCUS
CHEM