

RF6164 Four-stroke Motorcycle Oil Package

• Product Introduction

The four-stroke motorcycle oil package is composed of various high-quality detergents, dispersants, ZDDP and other additives. It has the good high temperature detergency, low temperature dispersity, anti-oxidation, anti-wear and other property. It can be used to lubricate three parts of engine, clutch and transmission at the same time; With different dosage in the appropriate base oil, can modulated 10w/30, 10w/40, 15w/40 level of oil, to meet API SL, SJ and other performance requirements.

• Recommended Dosage:

API Performance Level	Treating Rate (mass%)
SL	6.0%
SJ	5.5%
SG	5.0%
SF	4.5%

• Product Quality Characteristics & Test Method

Item	Typical Value	Test Method
Appearance	Brown viscous liquid	Visual Inspection
Density (20°C), kg/m ³	Report	GB/T13377, ASTM D4052
Kinematic Viscosity (100°C), mm ² /s	Report	GB/T265, ASTM D445
Flash Point (COC), °C	≥180	GB/T3536, ASTM D92
Total Base Number, mgKOH/g	100	SH/T0251, ASTM D2896
N Content, m%	0.8	SH/T0224, ASTM D3228
Zn Content, m%	2.1	GB/T17476, ASTM D4951
Ca Content, m%	3.1	GB/T17476, ASTM D4951
P Content, m%	1.8	GB/T17476, ASTM D4951

• Product Storage/Handling/Transportation/Package

Product storage temperature should not exceed 50 °C, the maximum temperature does not exceed 60 °C when handling and modulating;

This product is not flammable, non-explosive, non-corrosive, it is same as general petroleum products in safety, environmental protection, use and other aspects, no need the special protection.

Product packaging: 200L metal drum or according to user requirements packaging, the specific weight to the actual prevail.