

RF6312 Marine Cylinder Oil Package

• Product Introduction

RF6312 marine cylinder oil package use the best quality additives and it is developed according to advanced marine oil technology formula from the domestic and foreign. The product not only has excellent acid neutralization capacity and dispersity, wear resistance and oxidation stability, but also have excellent demulsibility, detergency, antifoam, anti emulsifying properties. Can meet the requirements for the special condition of marine cylinder oil. Practice has proved that the protective effect for marine cylinderis very notable and lasting.

• Recommended Dosage

Marine Cylinder Oil	Treating Rate (mass%)		
RF6312	40 TBN 50	40 TBN 65	50 TBN 70
	16%	21%	22%

• Product Quality Characteristics & Test Method

Item	Index	Test Method
Appearance	Brown viscous liquid	Visual Inspection
Kinematic Viscosity (20°C), mm ² /s	Report	ASTM D445
Flash Point (COC), °C	≥180	ASTM D92
Density (20°C), kg/m ³	10.91-13.33	ASTM D4052
Ca Content, m%	992-1032	ASTM D4951
Total Base Number, mgKOH/g	310-332	ASTM D2896

• Product Storage/Handling/Transportation/Package

During storage, loading/unloading and blending, the maximum temperature should not exceed 75°C. If storage for long time, the maximum temperature should not exceed 45°C. It is not flammable, not explosive, not corrosive, in the items of safety, environment protection, use, etc., it is same as normal petroleum product, with no special protection. Product package: The product is packed with 200 litre iron drum or according to user's requirement. Specific weight of delivery is subject to the actual filling weight.