

RF6340A Two-stroke Water-cooled Outboard Additive Package

Product Introduction

RF6340A two-stroke water-cooled outboard additive package is blended by excellent performance ashless additives, rust inhibitors and detergents. It has excellent lubricity, abrasion resistance, and outstanding smoke exhaust performance, satisfy the performance requirements of NMMA TC-W3.

Recommended Dosage:

Performance Grade	Dosage
NMMA TC-W3	19.8%

Product Quality Characteristics&Test Method

Item	Typical Value	Test Method
Appearance	Brown viscous liquid	Visual Inspection
Density (20°C) , kg/m ³	890	GB/T13377, ASTM D4052
Kinematic (100°C) , mm ² /s	162	GB/T265, ASTM D445
Flash Point (COC) , °C	≤200	GB/T3536, ASTM D92
TBN, mgKOH/g	24	SH/T0251, ASTM D2896
N content, m%	1.25	SH/T0224, ASTM D3228

Product Storage/Handling/Transportation/Package

The storage temperature should not exceed 50°C, the loading/unloading and blending temperature should not exceed 60°C.

It is not flammable, not explosive, not corrosive, in the items of safety, environment protection, use, etc, it is same as normal petroleum product, with no special protection.

Product package: The product is packed with 200 liter iron drum or according to user's requirement. Specific weight of delivery is subject to the actual filling weight